| 100 |     |   |
|-----|-----|---|
| 1   | 1   | 7 |
| _/  | 1   |   |
| -   | = 1 |   |

| ART AE ROSPACE LTD | Work Ord :   | 23370       |  |
|--------------------|--------------|-------------|--|
| scription Aft Cap  | Part Number: | D2646       |  |
| vg: D2046 Rev. B   | Qıy          | 40          |  |
| of:                |              | Page 1 of 1 |  |

| ер | Location | Procedure   | Ву   | Date     | Qty  |
|----|----------|---|--|----------|------|
| T) | DC       | Issue Traveler  | K)   | 15,0007  | 40   |
| 2  | PG       | Issue P/O: 2008014<br>Spin as per Dwg D2646<br>Material release note required   | 12   | esch 07  | 40   |
| J. | RG       | Receive and inspect for transit damage Ensure material release note is attached | the second secon | c5/06/c7 | 70   |
| 4  | QC6      | Inspect dimensions as per Dwg D2646   | 2  | areb 74  | 37   |
| 5  | GA       | Drill using DT8026 as per Dwg D2646. Open holes to 19/64*                       | m  | 506.34   | 35   |
| 3  | GA.      | Deburr _ Counter suite  | rul  | 15.00 29 | 37   |
| 7  | FP       | Acid etch and alodine as per QSI 005 4.1  | 1/1  | J5/7/4   |      |
| 3  | FP       | Powder Coat Gloss White (Ref: 4.3.5.1) as per QSI 005 4.3                       | nd   | (50111   | 28 5 |
| 9. | QC3      | Inspect Powder Coat   | A  | 2601-07  | 36   |
| 10 | GA       | Pick:  Oty Part Number Abs State Description  NAS1330C3KB116 Insert Nas14       |  | cc 0104  | 21   |
| 11 | QC5      | Inspect work to Step 10   | m  | 06 01 09 | 4    |
| 12 | PK       | Identify and Stock  | 111  | 06 01 09 | 4    |
| 13 | AC       | Cost / part:  | Sur  | 06-01-17 | 4    |
| 14 | DC       | Close W/O<br>Inspect Level 21   | 0  | 06/01/17 | 4    |

| :ev | Date     | Change                      |
|-----|----------|-----------------------------|
| C   | 98.01.16 | Changed Inspection Levels   |
| D   | 99.01.04 | Added Powder Coat           |
| E   | 00.06.22 | Removed P/O for powder coat |
| F   | 05.06.07 | Reformat                    |

vised By Approved

1

JLM

RE EASED

